

## CLAIMS

1. A computer system providing an object-based virtual machine environment, in which middleware runs successive applications on a single virtual machine, said system including storage for storing objects for running said applications, said storage being logically divided into three heaps:

a system heap which is not garbage collected;  
a middleware heap which is garbage collected; and  
a transient heap which is cleared inbetween successive applications.

2. The computer system of claim 1, wherein system classes for the virtual machine are loaded into the system heap, thereby providing subsequent applications with the ability to use these classes without having to reload them

3. The computer system of claim 2, wherein reusable objects other than class objects that must persist between successive applications are stored in the middleware heap.

4. The computer system of claim 1, wherein the middleware heap is garbage collected between successive applications.

5. The computer system of claim 4, wherein only the portion of storage corresponding to the middleware heap is garbage collected between successive applications.

5 6. The computer system of claim 1, wherein the transient heap is used for storing applications objects that are used for only the duration of the application.

10 7. The computer system of claim 6, wherein at the end of an application, any objects in the transient heap that are eligible for use by the next application, and which are referenced by live objects in the system heap or middleware heap, are promoted to the middleware heap.

15 8. The computer system of claim 6, further comprising a card table, in which each card corresponds to a portion of the middleware heap, and said card is marked if the middleware heap potentially references an object in the transient heap.

20 9. The computer system of claim 8, wherein each card corresponds to a memory region having a size greater than the minimum size for an object.

25 10. The computer system of claim 9, wherein a card is marked whenever an object in the corresponding memory region is updated.

11. The computer system of claim 1, further including a  
middleware classloader and an application class loader,  
wherein objects from classes loaded by the middleware  
classloader will be created in the middleware heap, and  
objects from classes loaded by the application classloader  
will be created in the transient heap.

12. The computer system of claim 11, further including one  
or more system classloaders, wherein objects from classes  
loaded by the one or more system classloaders are created  
in the middleware heap or the transient heap depending on  
the current context.

13. The computer system of claim 12, wherein the current  
context is middleware if the method being run derives from  
a class loaded by the middleware classloader, and  
application if the method being run derives from a class  
loaded by the application classloader.

14. The computer system of claim 13, wherein if the method  
being run derives from a class loaded by said one or more  
system classloaders, then the current context retains the  
value it had immediately before the method was run.

15. A method of operating a computer system providing an  
object-based virtual machine environment, in which

middleware runs successive applications on a single virtual machine, said system including storage for storing objects for running said applications, said method comprising the steps of:

5           logically dividing the storage into three heaps: a system heap, a middleware heap, and a transient heap;  
          performing garbage collection on the middleware heap and the transient heap, but not on the system heap; and  
          clearing the transient heap inbetween successive  
10       applications.

16. A computer program product comprising computer program instructions encoded on a computer readable media for loading into a computer system which provides an  
15       object-based virtual machine environment, in which middleware runs successive applications on a single virtual machine, said system including storage for storing objects for running said applications, said instructions causing the computer system to perform a method comprising the  
20       steps of:

          logically dividing the storage into three heaps: a system heap, a middleware heap, and a transient heap;  
          performing garbage collection on the middleware heap and the transient heap, but not on the system heap; and  
25       clearing the transient heap inbetween successive applications.